




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : B65B 55/06, 3/02	A1	(11) International Publication Number: WO 91/00826 (43) International Publication Date: 24 January 1991 (24.01.91)
(21) International Application Number: PCT/FI90/00181 (22) International Filing Date: 9 July 1990 (09.07.90) (30) Priority data: 893349 10 July 1989 (10.07.89) FI 895421 14 November 1989 (14.11.89) FI (71) Applicant (for all designated States except US): YHTYNEET PAPERITEHTAAT OY [FI/FI]; P.O. Box 70, SF-37601 Valkeakoski (FI). (72) Inventor; and (75) Inventor/Applicant (for US only) : STAHLECKER, Werner, U. [DE/DE]; Stafflenbergstrasse 3, D-7000 Stuttgart (DE). (74) Agent: OY KOLSTER AB; Iso Roobertinkatu 23, P.O. Box 148, SF-00121 Helsinki (FI).		(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE*, DE (European patent)*, DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI pa- tent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US. Published <i>With international search report.</i> <i>In English translation (filed in Finnish).</i>
(54) Title: A METHOD FOR FORMING A STERILE CONTAINER AND A CONTAINER WITH AN APERTURE WHICH IS SHUT WITH A CLOSURE (57) Abstract The invention relates to a method for forming a container, particularly a sterile container, which container comprises a container body (1) of a cardborad-based material and end parts (2, 3) attached to/formed at the ends thereof, in which meth- od a container body (1) is constructed, end parts (2, 3) are formed at/attached to the container body (1), a product to be packed is fed into the container body (1) through an aperture (5) at either end thereof, the aperture (5) is shut with a closure (4). To en- able easy shutting of the closure with a simple apparatus mechanism effecting the closing in addition to the fact that the possibility is offered to simultaneously steri- lize the container and the closure with uncomplicated equipment, the method of the invention is characterized in that the closure (4) is secured to the end part (2) prior to the feeding of the product to be packed into the container body (1). The invention al- so relates to a container.		



DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MC	Monaco
AU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LJ	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
DK	Denmark			US	United States of America

A method for forming a sterile container and a container with an aperture which is shut with a closure.

The invention relates to a method for forming a container, particularly a sterile container, which
5 container comprises a container body of a cardboard-based material and end parts attached to/formed at the ends thereof, in which method a container body is constructed, end parts are formed at/attached to the container body, a product to be packed is fed into
10 the container body through an aperture at either end thereof and the aperture is shut with a closure. The invention also relates to a container for liquids, particularly beverages, which container comprises a container body of a cardboard-based material and end
15 parts attached to/formed at the ends thereof.

Containers of the above described type, which, however, are not necessarily sterile, are known from Finnish Published Specification No. 65,962 and Finnish Patent Application No. 843665. When these con-
20 tainers are formed, one proceeds so that subsequent to the forming of the container body one end thereof is first closed and thereafter the container body is filled with the product to be packed, such as a liquid, possibly after the sterilization of the con-
25 tainer body. Thereafter also the other end of the container body is closed with a lid which is most commonly provided with an openable drinking or emptying aperture. When this kind of container is being formed, the closing of the upper end of the container
30 body after the filling of the container will present a problem. Then it should namely be possible to secure the lids to be affixed to the container bodies tightly to said container bodies without the product to be packed penetrating, e.g. spilling into, the
35 seam to be formed. If namely the container body has

become wet in its seam region, it is in practice difficult to raise the sealing temperatures and pressure with a container of the described type, particularly if the lid is of an insulating material such as cardboard, so high that liquid and oxygen proof seams could be reliably produced. The result is in any case a definite decrease in the production rate and deterioration of the quality of the product to be packed. Another problem in the filling method of a container of this kind will arise if one desires to make the container sterile. Then a sterilizing treatment corresponding to that performed on the container body has to be separately performed on the lid material. Furthermore, the steps pertaining to the joining of the lid material and the container body, such as the punching of the lid, forming, dust removal, insertion of the lid and other mechanical displacing movements, have to be performed in a sterile space or a space immediately adjoining such a space. Consequently, the construction of the packaging line becomes expensive.

Swiss Patent No. 580512 teaches a solution the purpose of which is to eliminate the above-stated problems. The publication discloses a solution wherein the end parts of the container are secured to the container body prior to the filling of the container, which is performed through a passage in the lid. The advantage with this solution is that the end parts can be secured to the container body so that the joint is liquid and air tight. The passage may be shut for instance with a separate closure, as has been disclosed in the patent. With a separate closure, the passage can be most securely shut. Yet the problem remains how the closing is to be effected in practice: an apparatus mechanism attending to the closing, constructed immediately in connection with

the filling will become uneconomical and particularly in a case where a sterile container is desired. Since in a sterile container also the closure must be sterile, it has been contemplated that the separate sterilizing equipment attending to the sterilization of the closure and the apparatus mechanism attending to the closing must be constructed within an aseptic space. However, in practice a complex apparatus unit of this kind does not warrant absolutely certain sterility. The solution according to Swiss Patent No. 580512 also has the problem that the weakening lines in the end part of the container must be torn open prior to the filling of the container to form a filling aperture, which in a case where the end parts are of a cardboard-based material results in that the absolute sterility of the container is lost.

The purpose of the present invention is to present a method for forming a container wherein the above-stated problems have been essentially eliminated, and thus a method for forming a container has been created which can be automated in a considerably simpler way than heretofore. The method according to the invention is mainly characterized in that the closure is secured to the end part before the product to be packed is fed into the container body.

The method of the invention is particularly well suited to forming a sterilized container, whereby it further includes, prior to the filling of the container body with a product to be packed, feeding of a sterilizing agent into the container body through said aperture and sterilizing of the closure, and removal of the sterilizing agent and drying of the container body and closure. It is thereby particularly advantageous to perform the sterilization of the closure simultaneously with the sterilization

of the container body. The advantageous embodiments of the method of the invention have been presented in the appended claims 2 to 7.

5 The container according to the invention is characterized in that an aperture has been formed in one of the end parts, and prior to the filling of the container a closure which leaves the aperture open has been attached to the proximity of the aperture, the size of said closure being sufficient to shut the
10 aperture. Advantageously, the end part including the aperture is of a cardboard-based material, in which case the cardboard at the edge of the aperture is covered with a plastic coating. The advantageous embodiments of the container of the invention have been
15 presented in the appended claims 10 and 11.

The invention is based on the idea of forming the closure in the end part of the container prior to the filling of the container, whereby a very simple apparatus mechanism effecting the closing may be
20 used, in addition to the fact that the possibility is offered to attend to the sterilization of the container as well as the closure in the same sterilizing treatment and even with the same sterilizing equipment. By disposing the closure for the aperture onto
25 the container exterior of the aseptic space prior to the sterilization and filling, a filling process is created which is very simple and economical in its stages of operation.

In the method of the invention, the aperture in
30 one end part of the container, which aperture may be either a drinking or an emptying aperture or some other aperture contemplated specifically for this purpose, is used both for supplying the product to be packed into the container body and possibly for supplying
35 the sterilizing agent into the container body,

emptying of the container body of sterilizing agent and interior drying of the container body. Both ends of the container are formed at/attached to the dry container body prior to the filling thereof, in which case the seams thereof can be easily made tight and entrance of the product to be packed between the lid and the container body when these are sealed together is avoided. When a sterile container is produced, the container body and its end parts are sterilized simultaneously. On account of the fact that the sterilizing agent is fed into a relatively closed environment, the use thereof can be made more effective. Also the hot air used in the drying can be better utilized. When the aperture in the end part is closed after the filling, no problems can arise from spilling of the content of the container, which could impair the tightness of the seal. The closure flap may be e.g. of plastic-aluminium laminate and it can be very simply heat-sealed to the end part. The container is alternatively suitable for sterilization by irradiation.

The following is a more detailed description of the method of the invention for forming a liquid container by means of an exemplary embodiment particularly contemplated as a liquid container, with reference to the accompanying drawing wherein

Figures 1, 3, 5, 6, 7 and 8 illustrate the different steps in the process according to the invention,

Figure 2 shows a cross-section of the end part in the proximity of an aperture in the end part,

Figure 4 illustrates the container prior to its filling, and

Figure 9 illustrates an exemplary container as produced.

Figure 1 shows a cylindrical container body 1 manufactured e.g. of a cardboard-based and plastic-coated material, having at least one side seam 8 formed therein which, when made with a sufficient overlap, ensures the tightness of the container body. An end part 2 having a drinking aperture 5 is shown in Figure 1 to be attached to one end of this container body 1. This end part 2, which has also been manufactured of a plastic-coated, cardboard-based material, has been pressed from an annular piece of material in the shape and size of the end of the container body. Thereby the edges 9 thereof have been bent by crimping substantially perpendicularly to the plane of the end part 2. This end part 2 is attached to the container body 1 in a conventional manner so that the end part 2 is introduced to some extent into the container body 1 and thereafter the outer edge of the container body is bent on top of the edges 9 of the end part 2 by crimping and heat sealed in this position. Such an attachment is apparent from Figure 2 on the one hand and also from the cross-sections shown in Figures 3 to 6.

Figure 2 shows a section of the end part 2 of the container in the proximity of the aperture 5. It is seen from the figure that at the edge of the aperture 5 the cardboard 10 is completely covered with a liquid and air proof coating, a plastic coating 11 serving as said coating. Instead of a plastic coating, some other liquid and air tight coating may be used.

Figure 3 shows the second step in the method of the invention, wherein the other end part 3 is attached to the container body 1. The attachment of this end part takes place fully similarly as that of the end part 2.

Figure 4 shows a container according to the invention, wherein a separate closure flap 4 has been disposed adjacent the filling aperture 5 in an upright position.

5 Figure 5 shows a step wherein a sterilizing agent 6 is fed into the container body 1 through an aperture 5 in the end part 2 thereof and to the closure flap 4. This sterilizing agent, which very often is hydrogen peroxide, can be fed either as a solution or by droplet spraying or as vapour. If the
10 sterilizing agent is fed as a solution, it must be poured out in the next step. If, on the other hand, the sterilizing agent is fed as droplet spraying or as vapour, no pouring out need to be carried out, but
15 the sterilizing agent can be removed in connection with the interior drying of the container body.

 This drying of the container body 1 has been illustrated in Figure 6. In this step, hot air is blown into the container body 1 through the aperture
20 5 in the end part 2 thereof and to the closure flap 4. This is a very advantageous way to dry the closure flap and on the one hand to dry the container body from within as well as to remove the used sterilizing agent from within the container body. If namely hydrogen peroxide has been used as a sterilizing agent,
25 when heated sufficiently by the action of the hot air fed in it will break down into water and oxygen which are entrained in the stream of hot air exiting from the container body in gaseous form. Both when the
30 sterilizing agent is supplied in accordance with Figure 5 and when the container body is dried from within in accordance with Figure 6, there is in practice advantage of the fact that also the upper end of the container body 1 is closed with a lid 2. Thereby
35 the sterilizing agent and the hot air, respectively,

are fed into a relatively closed space wherein they can act efficiently without escaping into the environment. In this way, the amount of both the sterilizing agent used and also the hot air needed for the drying can be diminished in comparison with a situation where the container body would be open at the upper end.

In the process step according to Figure 7, the liquid to be packed is fed into the sterilized container body through the aperture 5 in the end part 2 of the container body 1. In this way, the liquid to be packed 7 which is fed into the container body can no longer impair the seams between the container body 1 and the end parts 2 and 3 thereof.

Figure 8 shows the last step in the method of the invention, wherein the aperture in the end part 2 of the container body is covered with a closure flap 4. This closure flap may most preferably be of plastic-aluminium laminate which thus has a meltable plastic surface. When the closure flap 4 is pressed at a sufficiently high temperature, which may be at least 110°C, onto the edges of the aperture in the end part 2 of the container body 1, also having a layer of meltable plastic material, the closure flap 4 can be heat sealed very effectively and reliably to the surface of the end part 2. As has been shown in Figure 9, the closure flap 4 has been so shaped that it has a projection facilitating the tearing open thereof. If one wishes to use the aperture 5 also as a drinking or emptying aperture in this way, it is advantageous to use as the plastic material of the closure flap so called peelable polyethylene, in which case it can be relatively easily removed from the surface of the end part 2. As was already stated in the foregoing, the aperture 5 may also be an aper-

ture specifically contemplated for carrying out the method of the invention, in which case the intention is not to use it later for opening the container. Then the shape of the closure flap is naturally different, and also the material thereof may be selected differently. Thereby one of the end parts of the container body naturally includes suitable means for opening the container already prior to the attachment thereof to the container body 1.

10 In the above, the method according to the invention for forming a container has only been illustrated on the basis of one exemplary embodiment specifically pertaining to a liquid container and it is to be understood that the method of the invention can
15 be implemented irrespective of the nature of the product to be packed, the shape of the container body and the location or shape of the filling aperture in either end part of the container body. Thus also the closing of the ends of the container body may vary,
20 and e.g. in connection with a rectangular container body closing by means of flattening will naturally also come into question for one end. It is advantageous to make the aperture in the end part material prior to the attachment of the end part to the container body particularly when one wishes to protect
25 the edges of the aperture with a liquid and gas impervious layer. It can be contemplated that instead of an aperture, the forming of an opening is carried out for the part of substantial passages only.

C l a i m s :

1. A method for forming a container, particularly a sterile container, which comprises a container body (1) of a cardboard-based material and end parts (2, 3) attached to/formed at the ends thereof, in which method

a) a container body (1) is constructed,
b) end parts (2, 3) are formed at/attached to the container body (1),

c) a product to be packed (7) is fed into the container body (1) through an aperture (5) at either end thereof,

d) the aperture (5) is shut with a closure (4), characterized in that

e) the closure (4) is secured to the end part (2) before the product to be packed (7) is fed into the container body (1).

2. A method as claimed in claim 1, characterized in that it further comprises, prior to the filling of the container body (1) with the product to be packed (7),

feeding of a sterilizing agent (6) into the container body through said aperture (5) and sterilizing of the closure (4), and removal of the sterilizing agent and drying of the container body and closure.

3. A method as claimed in claim 2, characterized in that the closure (4) is sterilized simultaneously with the sterilization of the container body (1).

4. A method as claimed in claim 2 or 3, characterized in that the sterilizing agent (6) is fed into the container body (1) as drop-let spraying or as vapour and that the sterilizing

agent is removed and the container body and closure (4) are dried from within by blowing hot air into the container body through said aperture (5).

5 5. A method as claimed in claim 1, c h a r -
a c t e r i z e d in that it further comprises,
prior to the filling of the container body (1) with
the product to be packed (7), sterilization of the
container body (1) and closure (4) by irradiation.

10 6. A method as claimed in any one of the prec-
eding claims 2 to 5, c h a r a c t e r i z e d in
that a cardboard-based material is used as an end
part (2) including an aperture (5), the cardboard at
the edge of said aperture being covered with a plas-
tic coating.

15 7. A method as claimed in claim 1, c h a r -
a c t e r i z e d in that a closure flap (4) is
employed as the closure.

20 8. A method as claimed in claim 1, c h a r -
a c t e r i z e d in that the forming of the aper-
ture (5) in the end part is carried out at least for
the part of substantial passages prior to the secur-
ing of the end part to the container body (1).



25 9. A container for liquids, particularly bever-
ages, comprising a container body (1) of a cardboard-
based material and end parts (2, 3) attached to/
formed at the ends thereof, c h a r a c t e r -
i z e d in that an aperture (5) has been provided
in one of the end parts, and prior to the filling of
the container a closure (4) which leaves the aperture
30 open has been attached to the proximity of the aper-
ture, the size of said closure being sufficient to
shut the aperture.

35 10. A container as claimed in claim 9,
c h a r a c t e r i z e d in that the end part (2)
including the aperture (5) is of a cardboard-based

material, the cardboard (10) at the edge of the aperture being covered with a plastic coating (11).

11. A container as claimed in claim 9,
c h a r a c t e r i z e d in that the closure at-
5 tached to the proximity of the aperture (5) is cons-
tituted by a closure flap (4).

1/3






FIG. 5




FIG. 4




FIG. 6

- 3 / 3 -




FIG. 7




FIG. 8




FIG. 9

INTERNATIONAL SEARCH REPORT

International Application No PCT/FI 90/00181

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶ According to International Patent Classification (IPC) or to both National Classification and IPC IPC5: B 65 B 55/06, 3/02																													
II. FIELDS SEARCHED <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Minimum Documentation Searched⁷</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%; border-bottom: 1px solid black;">Classification System</td> <td style="border-bottom: 1px solid black;">Classification Symbols</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom;">IPC5</td> <td style="vertical-align: bottom;">B 65 B</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched⁸</div> <p>SE,DK,FI,NO classes as above</p>			Classification System	Classification Symbols	IPC5	B 65 B																							
Classification System	Classification Symbols																												
IPC5	B 65 B																												
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹ <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; border-bottom: 1px solid black;">Category</th> <th style="width: 60%; border-bottom: 1px solid black;">Citation of Document,¹¹ with indication, where appropriate, of the relevant passages¹²</th> <th style="width: 30%; border-bottom: 1px solid black;">Relevant to Claim No.¹³</th> </tr> <tr> <td style="vertical-align: top;">X</td> <td style="vertical-align: top;">US, A, 3943682 (RAUSING) 16 March 1976, see column 3, line 55 - line 61</td> <td style="vertical-align: top;">1-3,5-11</td> </tr> <tr> <td style="vertical-align: top;">Y</td> <td style="text-align: center; vertical-align: middle;">--</td> <td style="vertical-align: top;">4</td> </tr> <tr> <td style="vertical-align: top;">X</td> <td style="vertical-align: top;">US, A, 2355073 (J.M. HOTHERSALL) 8 August 1944, see the whole document</td> <td style="vertical-align: top;">1-3,5-11</td> </tr> <tr> <td style="vertical-align: top;">Y</td> <td style="text-align: center; vertical-align: middle;">--</td> <td style="vertical-align: top;">4</td> </tr> <tr> <td style="vertical-align: top;">X</td> <td style="vertical-align: top;">DK, B, 122801 (SCHMALBACH-LUBECA-WERKE AG) 17 April 1972, see page 2, line 9 - line 20</td> <td style="vertical-align: top;">1-3,5-8</td> </tr> <tr> <td style="vertical-align: top;">Y</td> <td style="text-align: center; vertical-align: middle;">--</td> <td style="vertical-align: top;">4</td> </tr> <tr> <td style="vertical-align: top;">Y</td> <td style="vertical-align: top;">FI, B, 48558 (EX-CELL-O CORPORATION) 27 August 1969, see the whole document</td> <td style="vertical-align: top;">4</td> </tr> <tr> <td></td> <td style="text-align: center; vertical-align: middle;">-----</td> <td></td> </tr> </table>			Category	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³	X	US, A, 3943682 (RAUSING) 16 March 1976, see column 3, line 55 - line 61	1-3,5-11	Y	--	4	X	US, A, 2355073 (J.M. HOTHERSALL) 8 August 1944, see the whole document	1-3,5-11	Y	--	4	X	DK, B, 122801 (SCHMALBACH-LUBECA-WERKE AG) 17 April 1972, see page 2, line 9 - line 20	1-3,5-8	Y	--	4	Y	FI, B, 48558 (EX-CELL-O CORPORATION) 27 August 1969, see the whole document	4		-----	
Category	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³																											
X	US, A, 3943682 (RAUSING) 16 March 1976, see column 3, line 55 - line 61	1-3,5-11																											
Y	--	4																											
X	US, A, 2355073 (J.M. HOTHERSALL) 8 August 1944, see the whole document	1-3,5-11																											
Y	--	4																											
X	DK, B, 122801 (SCHMALBACH-LUBECA-WERKE AG) 17 April 1972, see page 2, line 9 - line 20	1-3,5-8																											
Y	--	4																											
Y	FI, B, 48558 (EX-CELL-O CORPORATION) 27 August 1969, see the whole document	4																											

<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Special categories of cited documents:¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 50%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p> </div> </div>																													
IV. CERTIFICATION <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black;">Date of the Actual Completion of the International Search</td> <td style="width: 50%; border-bottom: 1px solid black;">Date of Mailing of this International Search Report</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom;">18th October 1990</td> <td style="vertical-align: bottom; text-align: center;">1990 -10- 1 9</td> </tr> <tr> <td style="border-bottom: 1px solid black;">International Searching Authority</td> <td style="border-bottom: 1px solid black;">Signature of Authorized Officer</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom; text-align: center;">SWEDISH PATENT OFFICE</td> <td style="vertical-align: bottom; text-align: center;"> Yvonne Siösteen </td> </tr> </table>			Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	18th October 1990	1990 -10- 1 9	International Searching Authority	Signature of Authorized Officer	SWEDISH PATENT OFFICE	 Yvonne Siösteen																			
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report																												
18th October 1990	1990 -10- 1 9																												
International Searching Authority	Signature of Authorized Officer																												
SWEDISH PATENT OFFICE	 Yvonne Siösteen																												

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.PCT/FI 90/00181**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 90-09-27
The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 3943682	76-03-16	AU-D- 7008174	75-12-18
		CA-A- 1018912	77-10-11
		CH-A- 580512	76-10-15
		DE-A-B-C 2428355	75-01-16
		FR-A-B- 2233229	75-01-10
		GB-A- 1446371	76-08-18
		JP-C- 1209370	84-05-29
		JP-A- 50036295	75-04-05
		JP-B- 58039690	83-08-31
		NL-A- 7407931	74-12-17
		SE-B-C- 383625	76-03-22
		SE-A- 7308364	74-12-16
US-A- 2355073	44-08-08	NONE	
DK-B- 122801	72-04-17	NONE	
FI-B- 48558	69-08-27	NONE	